

Calmag

PART OF
MONARCH WATER

CalSoft



METERED WATER SOFTENERS

5
YEARS
Parts
Warranty

12
MONTHS
Labour Warranty

Product Codes - Mini

Standard CALSOFT-MINI

22mm CALSOFT-MINI-HFK

Product Codes - Midi

Standard CALSOFT-MIDI

22mm CALSOFT-MIDI-HFK

Product Codes - Maxi


Standard CALSOFT-MAXI

22mm CALSOFT-MAXI-HFK

	MINI	MIDI	MAXI
Dimensions H x W x D	620 x 330 x 535	835 x 330 x 535	1075 x 330 x 535
No. of people	1 - 8	1 - 11	1 - 15
Capacity per regeneration @300ppm	2000L	3000L	4000L
Salt used per regen (approx)	2kg	2.8kg	3.5kg
Water used per regen (approx)	85 L	115 L	202 L
Max flow rate l/min with 15mm kit	50	50	50
Max flow rate l/min with 22mm kit	70	70	70
Max pressure recommended	5 bar	5 bar	5 bar
Salt storage capacity	15kg	25kg	35kg
Salt used	Tablet	Tablet	Tablet
Water hardness test kit included	✓	✓	✓
Connections	3/4" BSP or 1" BSP	3/4" BSP or 1" BSP	3/4" BSP or 1" BSP

The standard 1/2"/15mm installation kits are suitable for homes with a cold water storage tank. If however, your home has a combination boiler or direct hot water system we recommend the installation of our high flow 3/4"/22mm installation kit.


Each kit comes with inlet valve, outlet valve, bypass valve, washers and 2 x stainless steel hoses. We use stainless steel full bore hoses for maximum flow rates.



Product Codes

15mm kit

WS-INSTALL-KIT



Product Codes

22mm kit

HFK-22

Contact us for 28mm enquiries

sales@monarchwater.co.uk 01986 784 759